



CLASSIC 210.070.xxx/ 210.090.xxx/ 210.110.xxx - single door

Reinforced glassfibre polyester parts, sandwich construction, insulated with polyurethane foam core
 Corner posts of GRP with vertical c-rails
 Textured surface in grey RAL 7032
 Protection class IP 65


Vertical c-rails provided at the side wall and rear wall
 3-point locking device with burglary-resistant swing handle with profile cylinder to DIN 18252 (lockable)
 Roof overhang 25 mm all around

Arrangement

Floor (see data sheet Sd522-xe "Floor versions for classic series")

Options

- MP** Mounting plate
- FA/FS** Acrylic glass/ Safety glass window
- C-VA** Vertical c-rails in stainless steel instead of aluminium
- GO** Antistatic to avoid electrostatic charges according to EN IEC 60079-0
- F30** Fire resistance class F30
- SB** Floor fastening (see data sheet Sd523-xe "Fastenings for classic-floor versions design ...")
- WA** Wall fastening inside/ outside
- SZ** Ground vault



* clear width

scale 1:25

Type	H	Sizes (mm) with floor		
		B	b	T
210.070.050	2140	700	490	500
210.070.070				700
210.070.090				900
210.070.110				1100
210.090.050				900
210.090.070	700			

Type	H	Sizes (mm) with floor		
		B	b	T
210.090.090	2140	900	690	900
210.090.110				1100
210.110.050				1100
210.110.070		700		
210.110.090		900		
210.110.110	1100			