



Product Overview 2013 General Accessories for Cabinets

Sketch	Type Designation	Description	Cabinet Series	
Lighting equipment (damp-proof) 230Volt/ 50Hz				
	SHFR	Fluorescent tube with protective cover, on/off switch and socket-outlet combination and junction box, completely installed in the cabinet	1 x 18 watts, 340 mm long (small)	
		1 x 18 watts, 678 mm long		
		1 x 36 watts, 1288 mm long		
		1 x 58 watts, 1588 mm long		
		1 x 3 Watt 12 LEDs 400 mm long		
		Door contact switch instead of on/off switch	all	
FE102	Extra charge for additional socket			
	Special voltages, other designs			
	In Ex-Proof Version for hazardous areas			
Combination of filter fans & exhaust filters, fan allowing air to be blown into or out of cabinet (A) – damp room				
	Supply voltage 230 V/ 50 Hz, IP 55, UV-resistant, installed,		all	
	SLFL-PF22.000 /...A	Fan 145x145mm, air volume flow 56cbm/h (unrestricted)		
	SLFL-PFA20.000	Exhaust filter		
	SLFL-PF43.000 /...A	Fan 252x252mm, air volume flow 233cbm/h (unrestricted)		
	SLFL-PFA40.000	Exhaust filter		
	SLFL-PF65.000 /...A	Fan 320x320mm, air volume flow 505cbm/h (unrestricted)		
	SLFL-PFA60.000	Exhaust filter		
	FM139	Thermostat RT-SSR 10-60°C IP30		
FM099	Thermostat AZT-I 5-35°C IP54			
Combination of filter fans & exhaust filters, fan allowing air to be blown into (B) or out of cabinet (A) – Ex-version				
	Supply voltage 230 V/ 50 Hz, IP 54, UV-resistant, installed		all	
	SLFL-EXVENTB/...A and SLOO-Gitter	Fan and protection grid against contact 302x302mm		air volume flow in combination: 150 cbm/h
	SLFL-PF40.000 and SLOO-Gitter	Exhaust filter and protection grid against contact 302x302mm		
		Ex Thermostat		
Floor mounting equipment				
	SB007-WSA	External floor mounting bracket (Set=4 pcs.)	BASIC see data sheet SD526	
	SB010-WSA	Internal floor mounting (Set=4 pcs.)		
	SB035-WSA	Internal floor mounting (Set=4 pcs.)	CLASSIC see data sheet SD523	
	SB059-WSA	Internally with additional anchor plates (Set=4 pcs.)		
	SB020-WSA	Four mounting holes (1 pc.)		
	SB086-WSA	Welded straps, inside, with anchor dowels (Set=4 pcs.)		
	SB007-WSA	External mounting bracket (Set=4 pcs.)		
	SK008-WSA	With external lifting bracket (Set=4 pcs.)		
	SK0082-WSA	With external lifting bracket "heavy lift" (Set=4 pcs.)		
		Vault mounting (for underground vaults) see data sheet SD192 and SD292		
SB050	Standard mounting set for ground vault (1 set = 4 pcs.) tapered ground screws and fastening bracket suitable for soil classes I, II, III and V			
	Designed for other soil classes or increased requirements			
	INTERTEC stability calculation (customised)			
Wall mounting equipment				
	SW009	Inside	BASIC	
	SW141	Outside		
	SW001	Outside, for double doors		
	SW001	Outside, Series 110, width	CLASSIC	
		700 mm		
		900 mm		
		1100 mm		
	1350 mm			
	1550 mm			
	1750 mm			
	1950 mm			



Product Overview 2013 General Accessories for Cabinets

Swing-out mounting plates					
	Sheet steel, zinc coated 3 mm thick, with rolled edges, optionally hinged left or right, with double-bit lock and handle for opening, installed behind the door			CLASSIC	BASIC, with extra mounting rails behind the door
	Door (H x W)	Type Designation	Mounting-plates (H x W)		
	1000 x 600	SMPS-1000.400MS	850 x 350 mm		
	1000 x 800	SMPS-1000.600MS	850 x 550 mm		
	1000 x 1000	SMPS-1000.800MS	850 x 750 mm		
	1000 x 1200	SMPS-1000.1000MS	850 x 950 mm		
	1250 x 800	SMPS-1250.600MS	1100 x 550 mm		
	1250 x 1000	SMPS-1250.800MS	1100 x 750 mm		
	1250 x 1200	SMPS-1250.1000MS	1100 x 950 mm		
	1500 x 800	SMPS-1500.600MS	1350 x 550 mm		
	1500 x 1000	SMPS-1500.800MS	1350 x 750 mm		
	1500 x 1200	SMPS-1500.1000MS	1350 x 950 mm		
	1750 x 800	SMPS-1750.600MS	1600 x 550 mm		
	1750 x 1000	SMPS-1750.800MS	1600 x 750 mm		
	1750 x 1200	SMPS-1750.1000MS	1600 x 950 mm		
	2000 x 800	SMPS-2000.600MS	1850 x 550 mm		
	2000 x 1000	SMPS-2000.800MS	1850 x 750 mm		
2000 x 1200	SMPS-2000.1000MS	1850 x 950 mm			
Special designs or stainless steel material					
Swing-out mounting plates, depth-adjustable					
	Prices as before, however extra charge due to four additionally required horizontal mounting rails, see "Pricelist: Options and Configurations for Cabinets" page 3, or, for more detailed information, data sheet SD726				
19" Profiles, stainless steel, mounted behind the door					
	SM269	For door widths 600 mm For door widths 1000 mm (Option with side covers) Other door widths	BASIC/ CLASSIC		
19" Profiles, stainless steel, depth adjustable					
	Prices as above, however extra charge due to 4 additionally required horizontal mounting rails, see "Pricelist: Options and Configurations for Cabinets" page 3				
19"-Swing frame, stainless steel, installed in twin beams, hinged left or right, lockable					
	SM268	Without side covers With side covers, left <u>and</u> right With side cover, left <u>or</u> right	BASIC/ CLASSIC		
19"-Swing frame, stainless steel, depth adjustable, installed in twin beams, hinged left or right, lockable					
	Prices as above, however extra charge due to 4 additionally required horizontal mounting rails, see "Pricelist: Options and Configurations for Cabinets" page 3, or for more detailed information, data sheet SD732				

For other mounting arrangements and accessories consult factory

* UH = unit of height

Subject to technical changes, printing errors and price increases due to rising raw material costs. Not all the options can be combined.

The listed prices are ex works (INCOTERMS 2010), uncleared, packing extra, plus V.A.T. (if applicable).

Prices are subject to change without notice. Payment: 10 days 2 %, 30 days net.

Place of performance is Neustadt on the Donau and place of jurisdiction is Ingolstadt on the Donau, Germany